

The Open University of Sri Lanka Faculty of Engineering Technology Industrial Studies Program

Final Examination-2010/2011

AEX6233 Hydrology

Date

: 01-04-2011

Time

: 1400 - 1700 hours

Durations

: Three (03) hours



SECTION 2: Answer any four (04) questions. All questions carry equal marks.

- 1. Briefly explain application of Darcy's law use in ground water engineering.
- 2. What is "Dupuit" equation? State the assumptions that enter in its development. Explain the "Theis" formula and define well function?
- 3. A production well tapping an unconfined aquifer an initial saturated thickness of 8.2 m. A fully penetrating 25 cm diameter this well is pumped at rate of 65 liters per second until a steady state cone of depression is established. The draw down (from ground surface) measured at two observation wells situated 15 m and 31 m from the pumped well are then found to be 5.30 m and 4.90, respectively. Initial water level below the ground surface (level) is 3.50 m.
 - a. Determine the hydraulic conductivity and transmisivity of the aquifer
 - b. If all the observation points were on the Dupit curve, what was the stabilize water level from ground level in the production well.
- 4 Explain ground water availability in Sri Lanka and threats to groundwater quality in Sri Lanka with suitable diagram.
- Differentiate between shallow dug wells and deep tube wells. How are dug well constructed and explain how do they function using suitable diagram.
- 6 (a) Distinguish with sketches, the difference between an unconfined aquifer and a confined aquifer.
 - (b) What is meant by the term "radius of influence"?
 - (c) An unconfined aquifer has thickness of 35m. A fully penetrating 25 cm diameter well in this aquifer is pumped at a rate of 40 liters per second. The drawdown measured in two observation wells located at 10 m and 100m from well are 8.0 m and 0.5 m respectively. Determine the hydraulic conductivity of aquifer. At what distance from the well, the draw down is insignificant?